



PU single-component adhesive. MDI polyurethane prepolymer that reacts and dries with humidity. Used to glue plastic, rubber, wooden and metal elements, grass, etc.  
Furnished in 0.94kg bottles with an application cannula.

[Catalogue](#) | [HD image](#)

## Materials:

## Application:

1. Surfaces must be dry and free of dust, grease or dirt. As regards rubber tiles, the ground must have a minimum planimetry.
2. Gluing becomes effective after 4-5 days as the adhesive dries with humidity.
3. Do not keep the bottle open for an extended period of time.
4. Estimated consumption between 0.5 and 0.9 kg/m<sup>2</sup>. As regards rubber tiles, between 0.1 and 0.2 kg/m<sup>2</sup>.
5. Store in a cool and dry place, away from sun light.

## Specifications:

Water- and solvent-free.

Stock shelf life (1)

Free NCO content: 6%

Viscosity at 25°C <1700 cP.s (2)

1. Product must be stocked closed and at room temperature
2. Brookfield, 20 tr/min, spindle 3

## Security data:

Contains methylene diphenyl diisocyanate. Skin, eye and respiratory tract irritant. Avoid contact with eyes or skin and inhalation. In the event of contact, rinse immediately the affected area with water. It is recommended to use protection equipments and apply the product in a ventilated area.

R36 EYE IRRITANT

S26 IN THE EVENT OF EYE CONTACT, RINSE WITH WATER AND SEEK MEDICAL ATTENTION

S46 IN THE EVENT OF INGESTION, SEEK MEDICAL ATTENTION IMMEDIATELY AND SHOW THE LABEL OR BOTTLE TO THE DOCTOR

S2 KEEP OUT OF THE REACH OF CHILDREN

IN THE EVENT OF AN ACCIDENT, CONTACT THE TOXICOLOGICAL INFORMATION SERVICE, TEL : +34 (91) 562 04 20

These informations

Cette information corresponds to our current knowledge and should be used only as an initial guidance on our products and their applications. The text and technical data are used solely for information and advise purposes; à notre état actuel de connaissance et sert à titre d'indication sur nos produits et leurs possibles applications. Ce texte et les données techniques servent uniquement à informer et le conseiller sur l'utilisation du produit ; we are not to be held responsible for any accident or problem that may arise. It is always recommended to carry out application tests beforehand.

## Playful features:

